



Global ZZ 1567 Series ZIG-ZAG FANCY STITCH MACHINES


ZZ 1567

- High speed, cam controlled, fancy stitch zig-zag machine, standard supplied with 3 cams.
Extra: 16 optional cams.
- Máquinas de zig zag variable en puntadas de fantasía, de alta velocidad y controladas por levas intercambiables. Con la máquina se sirven 3 discos estándar con diferente patrón y existen otros 16 discos disponibles.
- Hochleistungs Zick-Zack Ziernahtmaschine durch Kurvenscheiben gesteuert. Standard mit 3 verschiedene Zierstich-Muster-Kurvenscheiben. 16 zusätzliche Muster-Kurvenscheiben sind lieferbar.
- Machine zig-zag à grande vitesse, point décoratif contrôlé par came, livré avec 3 cames de motifs différents. 16 cames librables en option.

ZZ 1567 AUT

- Same as ZZ 1567, but equipped with automatic thread trimmer, back tack and presser foot lifter. (all electric)
- La misma que ZZ 1567, pero equipada con corta-hilos automático, alza-prensatejas y remate automático. (eléctrico)
- Baugleich mit ZZ 1567, jedoch ausgestattet mit automatischem Fadenabschneider, Fußlüftung und Verriegelung. (elektrisch)
- Identique à la ZZ 1567, mais équipée avec coupe-fil, relevage de pied et arrêts automatiques (électromagnétique)

Standard with 3 patterns cams!



Cam 232



Cam 202



Cam 224

TECHNICAL SPECIFICATIONS

MACHINE SPEED
max 4000 spm

OILING SYSTEM
semi automatic

HOOK TYPE
large hook

STITCH LENGTH
max 5 mm

PRESSER FOOT LIFT
max 12 mm

NEEDLE TYPE
134 R

ZIG-ZAG WIDTH
max 10 mm

OPTIONAL EXTRA'S ZZ 1567:

- (PNEUMATIC)**
- puller (not on AUT version)
 - puller lift (not on AUT version)
 - needle cooling
 - presser foot lift
 - back tack

- (ELECTRIC)**
- presser foot lift (standard on AUT version)
 - back tack (standard on AUT version)

Global ZZ 1567 Series ZIG-ZAG FANCY STITCH MACHINES

The Global ZZ 1567 is a single needle high speed flatbed zig-zag machine with a variety of cams. This industrial machine is designed for decorative zig-zag stitching. The ZZ 1567 AUT is equipped with thread trimmer, back tack and presser foot lifter (electric).

Cam specification









4-Row feed dog for positive fabric control



































Easily inter-changeable cams

3 Standard cams with each machine model

Part no S080	Cam number	Pattern width mm		Stitch diagram 	Stitch diagram 
		MIN	MAX		
...674219	232	0	0	for adjusting	for adjusting
...674113	202	4.5	10		
...674124	224	4.5	10		

Extra available cams

...674114	203	4.5	10		
...674115	204	3.5	6		
...674116	205	4.5	10		
...674117	206	3.5	6		
...674118	211	4	6		
...674119	214	4	10		
...674120	218	2	5		
...674121	219	2	5		
...674122	220	3.5	6		
...674123	221	4.5	10		
...674125	229	2	6		
...674221	230	3.5	6		
...674226	052	2	4.5		
...674227	053	1	2.4		
...674228	054	1.5	4		
...674229	055	3.5	6		

SPECIFICATIONS ZZ 1567 SERIES

MODEL	MAX. STITCH WIDTH MM	PRESSER FOOT LIFT (MM)	SPACE TO RIGHT OF NEEDLE	NEEDLE SYSTEM	NEEDLE Nm	Nm Synthetic	Nm Cotton	MAX. SEWING SPEED	THREAD TRIMMING DEVICE
ZZ 1567	10	12	265	134 R	80-130	20/3	30/3	4000	—
ZZ 1567 AUT	10	12	265	134 R	80-130	20/3	30/3	4000	•